

KB110

Killbros

DUAL-AUGER GRAIN CART

*Excellent stability. Low center of gravity.
Narrow transport and SPEED.*



The design of the Model KB110 grain cart satisfies the needs of today's operations. Among its many features, the 18" horizontal and 20" vertical dual-auger unloading power, coupled with the enormous capacity of 1,100 bushels, make this grain cart able and willing to keep your operation moving smoothly during harvest.

KB110

Killbros

MODEL KB110 DUAL-AUGER GRAIN CART

1,100-BUSHEL CAPACITY*, UNLOADS OVER 600 BUSHELS PER MINUTE



- Dual-auger design consists of an 18" horizontal auger that force feeds the 20" vertical auger for high speed unloading. The 3/8" super-edged flighting adds to auger life.
- Flow gate indicator can easily be viewed from the tractor cab. Sliding flow gate system on horizontal auger allows for low startup torque and 100 percent shut off.
- Walking tandem duals straddle 30" or 36" rows and provide smooth transportation and minimal compaction through the field. The offset tandem design allows the duals to "walk over" uneven terrain.
- Extended auger reach and narrow transport width from the vertical auger design that folds across and down.
- Carrier bearings on horizontal auger are greaseable from outside of cart for easy maintenance.
- The upper auger features a spring-loaded bearing that aids auger alignment during folding. A hydraulic valve locking mechanism on the vertical auger ensures a secure fold joint for a positive seal.
- Auger-mounted halogen unloading light for nighttime visibility.
- Friction-clutch protected drive train for long-lasting, dependable service.
- Spring-loaded chain tighteners ensure constant tension for longer chain and sprocket life. Heavy-duty sprockets on the drive-train ensure positive torque and convenient serviceability.
- Chain oiler with see-through oil container for routine chain lubrication.
- Rear-viewing ladder with lower hinged section for easy access and convenient viewing of cart contents.
- Cleanout door on vertical auger and multiple sliding cleanout doors on horizontal auger provide quick and convenient cleaning.

Other Options

- Multi-directional hydraulic downspout unloads either straight down or outward for easier unloading (as shown on cover picture).
- Weather guard rollover tarp to protect grain.
- Scale package for accurate in-field weighing.
- Roll printer or downloader module for storage of your records.

SPECIFICATIONS

Model KB110 (1,100 bushel capacity)	
Total length	30' 10"
Total height	11' 10"
Loading side height	10' 10"
Height to tip of spout	14' 4"
Auger reach	7'
Vertical auger dia.	20"
Floor auger dia.	18"
Approx. empty weight	15,400 lbs
Loaded tongue weight	5,200 lbs

WHEEL AND TIRE OPTIONS

Model KB110	Transport Width
Tire/Wheel Size	
900/60 x 32	12' 11"
76/50.00 x 32	13' 10"
480/80 x 42 walking tandem duals	11' 8"
520/85 x 38 walking tandem duals	11' 8"
3' x 11' tracks (steel idler wheels)	12'

Stop by your nearest Killbros dealer today and check out the benefits of the KB110 Grain Cart.



www.allianceag.com

Alliance Product Group reserves the right to make changes in engineering, design and specifications at any time without notice or obligation.

*Capacities measured with #2 corn at 15% moisture (56 lb. test weight)



Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. We support the efforts of Farm Safety 4 Just Kids and all organizations that promote farm safety.

