

- 8 • The innovative rear hose carrier is standard with the hydraulic 45- and 60-foot cross-fold boom and keeps the extra-length hoses (necessary for boom height adjustment) securely stored and tangle free.
  - Motorized boom ball valves and strainer kit are standard.
- 9 • Hydraulic height adjustment features up to 48" of on-the-go height adjustment for crop clearance.
  - The standard-equipment hydraulic accumulator on the hydraulic-fold models cushions the boom over rough terrain for longer life.
- 10 • The optional foam marker or light-bar guidance system allows for precise spraying on every pass.
  - An available fencerow nozzle kit provides precision spray placement next to fencerows. Add an optional chemical inductor for easier mixing and a 50-gallon rinse tank for quickly and easily flushing the tank between uses.
  - Choice of single- or triple-nozzle bodies with either 15- or 20-inch spacings.
  - Standard ceramic nozzle tips provide longer life and greater spraying versatility than stainless steel tips.



### Top Air® Specifications for Models 500, 750 Elliptical Sprayers

	45' MANUAL-FOLD BOOM	45' or 60' HYDRAULIC CROSS-FOLD BOOM
TRANSPORT WIDTH	8'6"	13'
HEIGHT	8'2"	11' – 13'10"
LENGTH	13'8"	14'6"

Due to continuing improvement in the design and manufacture of Top Air products, all specifications contained herein are subject to change without notice.

See your Top Air dealer today for a closeup look at the features and values of all Top Air sprayers, or visit our Web site at [www.allianceag.com](http://www.allianceag.com). You'll find everything you want... and more.

